Appl. No. 10/647,521

Attorney Docket No. 10541-1832

II. Listing of Claims

1. (Currently Amended) A vehicle temperature control system, comprising:

a housing having an intake opening for air intake and an output opening for

output air;

an evaporator core disposed in the housing and in fluid communication with

the intake opening;

a heater core disposed in the housing downstream from the evaporator

core and in fluid communication with the evaporator core, defining a space

between the evaporator core and the heater core, the heater core having a first

portion and a second portion; and

a separation wall having a first end and a second end, the first end being

attached to the first portion of the heater core and extending therefrom along the

length of the heater core towards the output in the space between the evaporator

core and the heater core.

2. (Original) The system of claim 1 wherein the heater core has an input face

and an output face and wherein the separation wall defines a flow channel from

the evaporator core to the input face of the heater core.

(Original) The system of claim 1 wherein the evaporator core and the 3.

heater core are in side by side relationship.

BRINKS HOFER GILSON & LIONE

Attorney Docket No. 10541-1832

Appl. No. 10/647,521

4. (Original) The system of claim 1 wherein the evaporator core has an input

side and an output side, the input side being adjacent to the intake opening and

the output side being adjacent to the separation wall.

5. (Original) The system of claim 4 further comprising of a blower disposed in

the housing and upstream from the evaporator core for introducing air into the

input side of the evaporator core.

6. (Original) The system of claim 1 wherein the housing is a drain area

adjacent to the evaporator core for condensation and a drain hole formed through

the housing for condensation drainage.

7. (Original) The system of claim 1 wherein the separation wall isolates a cold

air portion and a hot air portion of the space between the evaporator core and the

heater core, the cold air portion being adjacent to evaporator core and the hot air

portion being adjacent to the heater core.

8. (Currently Amended) [[The]] A vehicle temperature control system, of claim

7 comprising:

a housing having an intake opening for air intake and an output opening for

output air;

an evaporator core disposed in the housing and in fluid communication with

- 4 -

the intake opening;

BRINKS HOFER GILSON &LIONE Appl. No. 10/647,521

Attorney Docket No. 10541-1832

a heater core disposed in the housing downstream from the evaporator

core and in fluid communication with the evaporator core, defining a space

between the evaporator core and the heater core, the heater core having a first

portion and a second portion;

a separation wall having a first end and a second end, the first end being

attached to the first portion of the heater core and extending therefrom along the

length of the heater core in the space between the evaporator core and the heater

core;

wherein the separation wall isolates a cold air portion and a hot air portion

of the space between the evaporator core and the heater core, the cold air portion

being adjacent to evaporator core and the hot air portion being adjacent to the

heater core; and

wherein the separation wall defines a mixing channel for mixing cold air

and hot air, the mixing channel being downstream and in fluid communication with

the cold air portion and the hot air portion.

9. (Withdrawn)

10. (Withdrawn)

(Original) The system of claim 8 wherein the mixing channel is a first mixing 11.

- 5 -

channel and the separation wall is a first separation wall.

BRINKS HOFER &LIONE

- 12. (Original) The system of claim 11, wherein the second portion of the heater core is spaced apart from the housing forming a hot air entrance.
- 13. (Withdrawn)
- 14. (Withdrawn)
- 15. (Withdrawn)
- 16. (Withdrawn)
- 17. (Withdrawn)